

PR-202A



Especificaciones		
Modelo		PR-54
AC Current (A)	2A/20A/200A/400A 20A/200A/600A	±(1.5%+5)
AC Voltage (V)	2V/20V/200V/600V	±(1.2%+5)
DC Voltage (V)	200mV/2V/20V/200V/600V	±(0.8%+1)
Resistance (Ω)	200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ	±(0.8%+3)
Temperature (°C)	-40°C ~ 1000°C	
Temperature (°F)	-40°F ~ 1832°F	
Features		
Display Count		1999
Auto Range		
Manual Range		✓
Jaw Capacity		28mm
Diode		✓
Auto Power Off		
Continuity Buzzer		✓
Low Battery Indication		✓
Data Hold		✓
MAX Mode		✓
MIN Mode		✓
Full Icon Display		
Input Impedance for DCV	Around 10MΩ	✓
General Characteristic		
Power	PR-202A-9V Battery (6F22)	
LCD Size	35.6X 18mm	
Product Color	Red and Grey	
Product Net Weight	220g	
Product Size	210mm X 75.6mm X30 mm	
Standard Accessories	PR-202A-Batteries, Test Lead, Carrying Bag	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	40 PCs	
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)	
Standard Carton Gross Weight	23Kg	