

## Wall mounted receptacle

Part no. 27002



- screw terminals
- external fixing
- cable entry at top

## Technical specifications

|                           |                 |
|---------------------------|-----------------|
| Ampere                    | 16 A            |
| Poles                     | 4 p             |
| Voltage                   | 400 V           |
| Clock position            | 6 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 246 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

## Drawing

| Drawing<br>1 MB 463 | Amp.<br>Poles                                                 | 16   |       |       | 32    |       |       |
|---------------------|---------------------------------------------------------------|------|-------|-------|-------|-------|-------|
|                     |                                                               | 3    | 4     | 5     | 3     | 4     | 5     |
| Dim. in mm          | a                                                             | 95   | 93    | 92.5  | 102   | 102   | 102   |
|                     | b                                                             | 73.5 | 87.5  | 87.5  | 94    | 94    | 94    |
|                     | c                                                             | 93   | 107.5 | 110   | 115.5 | 115.5 | 119.5 |
|                     | d                                                             | 55.5 | 55.5  | 55.5  | 62    | 62    | 62    |
|                     | e                                                             | 61   | 76    | 76    | 84    | 84    | 84    |
|                     | f1                                                            | 5.3  | 5.3   | 5.3   | 5.1   | 5.1   | 5.1   |
|                     | f2                                                            | 5.3  | 5.3   | 5.3   | 5.1   | 5.1   | 5.1   |
|                     | h                                                             | 139  | 139   | 136.5 | 160   | 160   | 156.5 |
|                     | i                                                             | 19.8 | 21.5  | 21.5  | 26.5  | 26.5  | 26.5  |
|                     | M                                                             | M20x | M25x  | M25x  | M25x  | M32x  | M32x  |
|                     | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1.5  | 1.5   | 1.5   | 1.5   | 1.5   | 1.5   |
|                     |                                                               | 1.5  | 1.5   | 1.5   | 2.5   | 2.5   | 2.5   |
|                     |                                                               | -4   | -4    | -4    | -6    | -6    | -6    |