

For direct coupling to AF190, AF205 3-pole contactors



KPR-101L

- Manual or automatic reset selectable
- Phase loss sensitive acc. to IEC/EN 60947-4-1
- TEST and STOP function – Trip indication on the front
- Temperature compensation
- Suitable for three- and single-phase applications

Setting range	For contactors	Trip class	Catalog number	Global reference code	Weight (1 pce)
A					kg
66 ... 90	AF190, AF205	10A	TA200DU90	1SAZ421201R1001	0.755
80 ... 110	AF190, AF205	10A	TA200DU110	1SAZ421201R1002	0.760
100 ... 135	AF190, AF205	10A	TA200DU135	1SAZ421201R1003	0.760
110 ... 150	AF190, AF205	10A	TA200DU150	1SAZ421201R1004	0.760
130 ... 175	AF190, AF205	10A	TA200DU175	1SAZ421201R1005	0.770
150 ... 200	AF190, AF205	10A	TA200DU200	1SAZ421201R1006	0.785

For thermal overload relays	Description	Catalog number	Global reference code	Weight (1 pce) kg
A				
TA200DU (1)	Terminal shroud	LT200A185	1SAZ401901R1001	0.090
TA200DU	Single mounting kit	DB200	1SAZ401110R0001	0.225
TA200DU	Mechanical lug kit, 1 conductor/phase	EHTK210	(2)	0.118
TA200DU	Reset push button (3)	KPR-101L	1SFA616162R1014	0.027

(3) Note: for more information see catalog 1SXU000023C0202 Rev. A.

[illegible]